

NK 500, NK 500ESC

- ▶ For small and medium trucks 17m³ ~ 25m³
- ▶ HT-500 Series have the reliability, high airflow and capacity to protect the product load.
- ▶ Separated unit type with condenser and evaporator
- ▶ Compressor is powered with vehicle engine and electric devices.
- ▶ Front mount condenser:
 - ABS case, weight less, protection from rust, new round design.
- ▶ Slim Ceiling Evaporator:
 - ABS case, Maximum load space and high airflow volume with two fans.
- ▶ Cab Command In-control box with simple on/off switch and digital thermometer.
- ▶ ESC: Electric standby unit is installed in the condenser.
- ▶ Refrigerant Option: HFC R-134A / R-404A Chlorine zero

NK 500



- Front Mount Condenser
- Weight : 37kg

NK 500ESC



- Electric standby unit is installed within the condenser
- Weight : 133kg



- Slim Ceiling Evaporator
- Weight : 34kg



- Standard evaporator with three fans gives high air flow
- Weight : 31kg



- Cab command in-cab control box

Technical Data

Cooling Capacity	Temperature		Load Operation		Electric Operation	
		°C	Kcal/h	Watt	Kcal/h	Watt
38°C Ambient	R-404A	0	4,032	4,689	3,402	3,956
		-10	2,200	2,559	1,638	1,905
		-20	1,638	1,905	1,134	1,319
Compressor	Model		Seltec TM-16HS			
	No. of Cylinder		6			
	Displacement(cm ³)		163cc			
Refrigerant	R-404a 2.6kg					
Airflow	2,300 m ³ /h					
AC Motor	DC Voltage Option		DC 12V / DC 24V			
	AC Voltage Option		220V/240V/380V/415V, 1P/3P, 50/60Hz			
Defrost	2.2kW(3HP)					
			Automatic hot gas defrost initiated & terminated by cab controller			